



H3C MSR3600 ICT Converged Gateway

ICT Converged Gateway Router

Release Date: Jan 2024



New H3C Technologies Co., Limited

Product overview

H3C MSR3600 ICT Converged Gateway series integrates computing and storage capabilities and offers an open operating architecture. It can fast integrate with third-party customized applications to improve service processing efficiency and reliability at remote sites. The MSR3600 has the following benefits:

- CT and IT integration—Runs the industry-leading H3C Comware network operating system and integrates computing and storage capabilities to simplify network deployment and lower the total cost of ownership (TCO).
- Professional x86 hardware virtualization platform—Uses resource pools to manage hardware resources including CPU, memory, storage, and interface to enable flexible and dynamic resource allocation and adjustment based on the actual requirements.
- Unified AD-EC management platform—Supports unified management of both CT and IT services to improve maintenance efficiency.
- Service online release—Supports fast online release and deployment of new services through the AD-EC platform at any time without service interruption.
- Open architecture—Supports standard Windows or Linux for fast service integration. The AD-EC platform also provides open APIs for users to develop new applications and value-added services.

The MSR3600 ICT Converged Gateway series has two models: MSR3610-I-DP and MSR3610-IE-DP.



MSR3610-I-DP/MSR3610-IE-DP

Features and benefits

Next Generation CT and IT integration

- Runs H3C's state-of-art Comware network operating system and supports security, switching, wireless, and routing services.
- Integrates computing and storage capabilities and supports an external drive.
- Uses a professional hardware virtualization platform to group hardware resources including CPU, memory, storage, and interface in resources pools to enable flexible and dynamic resource allocation and adjustment based on the actual requirements.

Unified AD-EC management platform

- Device management and operating status monitoring—Manages versions, configurations, groups, and regions.



- CT service management—Configures VPN services, monitors operation state, controls bandwidth, and analyzes app statistics.
- IT services management—Performs computing and storage resource status monitoring, service status management (start, stop, and restart), and new service online release.

Fast deployment from USB drive

Supports CT and IT service deployment from a USB drive, making it possible to deploy a large number of MSR3600 gateways in a short time.

Rich interfaces for network expansion

- Provides GE copper, GE fiber, RS232, Provides multiple slots for port expansion.

Open architecture

- Supports the standard Windows, CentOS, Ubuntu, and RedHat operating systems for quick and smooth integration with customized services of third parties.
- Provides open RESTful APIs on the AD-EC platform for third parties to develop application-layer and value-added services.

Technical specifications

Hardware specifications

Item	MSR3610-I-DP+DDR4-8GB	MSR3610-IE-DP+DDR4-16GB
IP Forwarding Performance (IMIX)	3.8 Gbps	3.8 Gbps
Forwarding Performance with ACL+NAT+QOS (IMIX)	2.5 Gbps	3.5 Gbps
IPSec Forwarding Performance (1400byte)	780 Mbps	1.5 Gbps
CPU	X86, Quad-core, 2.2 GHz	X86, eight-core, 2.2 GHz
Memory (default/maximum)	8 GB	16 GB
Flash	4 GB (EMMC)	64 GB (EMMC)
HDD slot (2.5 inch)	1	1
USB port	1(USB3.0)	1(USB3.0)
Console port	1	1

Item	MSR3610-I-DP+DDR4-8GB	MSR3610-IE-DP+DDR4-16GB
WAN ports	2 × GE combo ports	2 × GE combo ports
LAN ports	6 x GE ports(can be configured as WAN interfaces)	6 x GE ports(can be configured as WAN interfaces)
SIC slot	4	4
Performance(1518B)	3.9 Gbps	3.9 Gbps
Operating system	Support for KVM Support for Windows, CentOS, Ubuntu, and RedHat	Support for KVM Support for Windows, CentOS, Ubuntu, and RedHat
Max power consumption	54 W	54 W
Power redundancy	Supported	Supported
Power voltage	AC: 100 VAC to 240 VAC @ 50 Hz/60 Hz	AC: 100 VAC to 240 VAC @ 50 Hz/60 Hz
Height	1 RU	1 RU
Dimensions (H × W × D)	43.6 × 440 × 360 mm (1.72 × 17.32 × 14.17 in)	43.6 × 440 × 360 mm (1.72 × 17.32 × 14.17 in)
Operating temperature	Without a hard disk: 0°C to 45°C (32°F to 113°F) With hard disk: 5°C to 40°C (41°F to 104°F)	
Operating humidity	Without a hard disk: 5% RH to 95% RH, non-condensing With a hard disk: 10% RH to 80% RH with hard disk, non-condensing	
Storage temperature	-40°C to +70°C (-40°F to +158°F)	
EMC	FCC Part 15 (CFR 47) CLASS A ICES-003 CLASS A VCCI-3 CLASS A VCCI-4 CLASS A CISPR 22 CLASS A EN 55022 CLASS A AS/NZS CISPR22 CLASS A CISPR 24 EN 55024 EN 61000-3-2 EN 61000-3-3 EN 61000-6-1 ETSI EN 300 386 EN 301 489-1	



Item	MSR3610-I-DP+DDR4-8GB	MSR3610-IE-DP+DDR4-16GB
Security	EN 301 489-17	
	UL 60950-1	
	CAN/CSA C22.2 No 60950-1	
	IEC 60950-1	
	EN 60950-1/A11	
	AS/NZS 60950	
	EN 60825-1	
	EN 60825-2	
	FDA 21 CFR Subchapter J	
	GB 4943	

Software specifications

Item	Specification
Layer 2 switching	Ethernet, Ethernet II, VLAN, 802.1p, 802.1Q, 802.1X, STP (802.1D), RSTP (802.1w), MSTP (802.1s), PPP, PPPoE Client, and PPPoE Server
IP services	Unicast/multicast, TCP, UDP, IP option, IP unnumbered, policy-based routing, and NetStream
	ECMP UCMP
IP application	Ping, Tracert, ICMP, DHCP server, DHCP relay, DHCP client, DNS client, DNS proxy, DDNS, NTP, and SNTP
	Static routing Dynamic routing: RIPv1/v2, OSPFv2, BGP, IS-IS
IPv4 routing	Route iteration
	Policy routing
	Multicast routing: IGMPv1/v2/v3, PIM-DM, PIM-SM, MBGP, MSDP
	IPv6 ND, IPv6 PMTU, IPv6 FIB, IPv6 ACL, NAT-PT, 6PE, and DS-LITE
IPv6	IPv6 tunneling: manual tunneling, automatic tunneling, GRE tunnel, 6to4, ISATAP
	Static routing
	Dynamic routing: RIPng, OSPFv3, IS-ISv6, BGP4+ IPv6 multicast: MLDv1/v2, PIM-DM, PIM-SM
QoS	LR
	Committed access rate (CAR) FIFO, WFQ, CBQ

Item	Specification
Security	Generic Traffic Shaping (GTS)
	Traffic classification
	Portal, 802.1X
	Local authentication, RBAC, RADIUS, TACACS+
	Basic Firewall Function, ASPF, ACL, filter, connection limit
	IKE, IPSec
	ADVPN, GDVPN, SSL VPN
	L2TP, NAT, PKI, RSA, SSHv1.5/2.0, URPF, mGRE, GRE
	ARP attack prevention
	Endpoint Admission Defense (EAD)
MPLS	AES, DES, 3DES, MD5, SHA1
	LDP, Static LSP
	L3VPN: MCE/multirole host
	L2VPN: Martini, Kompella, CCC PWs and static PWs
High availability	VRRP, VRRPv3
	Bandwidth-based load balancing and backup
	IP address-based load balancing and backup
	NQA collaboration with routing, VRRP or interface backup
	SNMP v1/v2c/v3, MIB, SYSLOG, RMON
Management and maintenance	BiMS remote management, booting from USB drive
	CLI, file system, and dual image
	DHCP, FTP, HTTP, ICMP, UDP public, UDP private, TCP public, TCP private, SNMP
	Console port login, Telnet (VTY) login, SSH login, and FTP login
Virtualization	EAA
	Integration of a highly available and high-performance open virtualization platform that supports third-party operating systems, such as Windows, CentOS, Ubuntu, and RedHat
	Complete lifecycle management of virtual machines, including VM creation, modification, startup, pause, recovery, hibernation, reboot, shutdown, and power-off
	Monitoring of critical VM resources, such as VM CPU, memory, disk I/O, and network I/O
	Support of high-performance virtualization Ethernet adapter and SR-IOV to virtualize the physical Ethernet adapter into several virtual adapters for VMs
Support of fast app deployment, app deployment to VMs through USB disk, and unified app deployment throughout the network	



Item	Specification
	Complete troubleshooting and recovery mechanism
	Scheduled backup and manual backup
	Real-time monitoring of VM state
	VM anomaly detection and auto reboot

Ordering information

Product ID	Description
RT-MSR3610-I-DP+DDR4-8GB	H3C MSR3610-I-DP ICT converged gateway + DDR4 8GB memory
RT-MSR3610-IE-DP+DDR4-16GB	H3C MSR3610-IE-DP ICT converged gateway + DDR4 16GB memory
Disk	
HDD-500G-SATA-3G-5.4K-SFF	500GB 2.5inch SATA HDD HardDisk Module
HDD-2T-SATA-6G-5.4K-SFF	2TB 2.5inch SATA HDD HardDisk Module
SIC module	
RT-SIC-4GSWF	4-port 100BASE-FX/1000BASE-X(SFP) Ethernet L2/L3 SIC Module
RT-SIC-4GSW	4-Port 10/100/1000BASE-T L2 Switch SIC Module
RT-SIC-2SAE	2-port Enhanced Sync/Async Serial SIC Module
RT-SIC-4SAE	4-port Enhanced Sync/Async Serial SIC Module
RT-SIC-1E1-F-V3-H3	1-Port Fractional E1 Interface SIC Module
RT-SIC-2E1-F-H3	2-Port Fractional E1 Interface SIC Module
RT-SIC-4G-CAT6	4G LTE CAT6 SIC module



The Leader in Digital Solutions

New H3C Technologies Co., Limited

Beijing Headquarters

Tower 1, LSH Center, 8 Guangshun South Street, Chaoyang

District, Beijing, China

Zip: 100102

Hangzhou Headquarters

No.466 Changhe Road, Binjiang District, Hangzhou, Zhejiang,

China

Zip: 310052

Tel: +86-571-86760000

Copyright ©2024 New H3C Technologies Co., Limited Reserves all rights

Disclaimer: Though H3C strives to provide accurate information in this document, we cannot guarantee that details do not contain any technical error or printing error. Therefore, H3C cannot accept responsibility for any inaccuracy in this document.

H3C reserves the right for the modification of the contents herein without prior notification

<http://www.h3c.com>